

Terminal/External Antennas				WiFi6E & WiFi7
Pacifica SREI038				
Antenna illustration (Not To Scale)				
Product Name	Pacifica Fixed (IP67)	Pacifica Swivel	Pacifica Cable (IP67)	Nitida
Part no	SREI038-IPP*	SREI038-S9P*	SREI038-xxP**	SRE3W084
Frequency	432-434 MHz	432-434 MHz	432-434 MHz	2.4 - 7.125GHz
Dimensions LWH (mm)	143.7 x 22.5 max.	152.56 x 22.5 max.	138.5 x 22.49 max. excluding cable	123.7 x 12.7 x 12.1 (mm3)
VSWR	1.60:1	1.65:1	1.80:1	1.6:1 / 1.8:1 / 2.3:1
Efficiency	50%	50%	50%	70% / 58% / 55%
Comments	*Additional part numbers for antennas with non standard connectors: SMA Plug Reverse: SREI038-xxR, SMA Jack: SREI038-xxJ, SMA Jack Reverse: SREI038-xxK **Four cable lengths available, part numbers are: 1.0m cable: SREI038-10P, 1.5m cable: SREI038-15P, 1.7m cable: SREI038-17P, 2.0m cable: SREI038-20P			

Implementation support




Antenova offers a full range of development support and RF testing to help reduce customization, design costs and accelerate your time to market. Antenova recommends customers to use our know-how when it comes to implementing the antenna. We offer advanced measuring equipment, custom tuning and technical support to obtain a secure and reliable implementation. Make Antenova your partner of choice for new product development.

Contact sales@antenova.com, and why not join our antenna design community at ask.antenova.com.

Antenova Limited, Global HQ
 Titan Court, 3 Bishop Sq, Hatfield, AL10 9NA, UK
T: +44 (0)170 7927 589
E: sales@antenova.com
W: www.antenova.com

Terminal/External Antennas

Draco SREI036 / Rabo SRELO62

Product Name	Draco Fixed (IP67)	Draco Swivel	Draco Cable (IP67)	Rabo Fixed (IP67)	Rabo Swivel
Antenna illustration (Not To Scale)					
Part no	SREI036-IPP*	SREI036-S9P*	SREI036-xxP**	SRELO62-IPP	SRELO62-S9P
Frequency	698-960 MHz 1427-1660 MHz 1720-2170 MHz 2300-2400 MHz 2500-2690 MHz	698-960 MHz 1427-1660 MHz 1720-2170 MHz 2300-2400 MHz 2500-2690 MHz	698-960 MHz 1427-1660 MHz 1720-2170 MHz 2300-2400 MHz 2500-2690 MHz	617-960MHz 1426-1660MHz 1710-2170MHz 2300-2400MHz 2500-2690MHz 3200-3800MHz	617-960MHz 1426-1660MHz 1710-2170MHz 2300-2400MHz 2500-2690MHz 3200-3800MHz
Dimensions LWH (mm)	143.7 x 22.5 max.	152.56 x 22.5 max.	138.5 x 22.49 max. excluding cable	143.7 x 22.5 x 13.5	132.61 x 30.75 x 13.5
VSWR	3.30:1	3.25:1	2.60:1	1.301-2.60:1	1.55:1-2.30:1
Efficiency	55%	%6	45%	75%	75%
Comments	* Additional part numbers for antennas with non standard connectors: SMA Plug Reverse: SREI036-xxR, SMA Jack: SREI036-xxJ, SMA Jack Reverse: SREI036-xxK ** Four cable lengths available, part numbers are: 1.0m cable: SREI036-10P, 1.5m cable: SREI036-15P, 1.7m cable: SREI036-17P, 2.0m ca-ble: SREI036-20P				

Implementation support

Antenova offers a full range of development support and RF testing to help reduce customization, design costs and accelerate your time to market. Antenova recommends customers to use our know-how when it comes to implementing the antenna. We offer advanced measuring equipment, custom tuning and technical support to obtain a secure and reliable implementation. Make Antenova your partner of choice for new product development.

Contact sales@antenova.com, and why not join our antenna design community at ask.antenova.com.



Antenova Limited, Global HQ
Titan Court, 3 Bishop Sq, Hatfield, AL10 9NA, UK
T: +44 (0)170 7927 589
E: sales@antenova.com
W: www.antenova.com